

Fire Controllers

Australian Standard Fire Status Panel

The Muirhead® Fire Status Panel is designed and built to the latest Australian Standards AS5062.

The panel will monitor the status of the fire bottle from two pressure switch inputs.

The low pressure input warns the operator when the bottle pressure is below the desired KPA level.

The shutdown pressure switch will trigger when the bottle has been discharged. It also has a key switch for override and push button for extended shutdown when activated.



Features

- Multi Voltage
- Solid State Technology
- Programmable shutdown
- One Shot Extension
- Key Switch Override
- IP65 Panel

Specifications

IP	IP65
Dimensions	120mm x 80mm x 55mm
Weight	0.5 kg

Parts

- | | |
|-------------|---|
| ↶ APN: 0475 | PRESSURE SWITCH 1200KPA FALLING 1/8NPT DUAL CIRCUIT |
| ↶ APN: 2348 | PRESSURE SWITCH 900KPA FALLING 1/8NPT DUAL CIRCUIT |
| ↶ APN: 4800 | PRESSURE SWITCH 200KPA FALLING 1/8NPT DUAL CIRCUIT |
| ↶ APN: 5236 | PRESSURE SWITCH 1050KPA FALLING 1/8NPT DUAL CIRCUIT |
| ↶ APN: 5884 | FIRE SHUTDOWN CONTROLLER MULTI VOLTAGE AS5062 SPECIFICATION |

Reference: SBMH0615117



RCT
Head Office
Unit 1-5/511 Abernethy Rd
Kewdale WA 6105, Australia
sales@rct-global.com

Australia +61 8 9353 6577
Africa +27 83 292 4246
Canada +1 705 590 4001
Central Asia +7 910 411 1174
USA +1 801 938 9214
South America +56 22 4423 6600

Copyright © 2023 Remote Control Technologies Pty Ltd. Images for illustration purposes only. Discover more @ rct-global.com